

FLUSH DOOR RANGE COMPARISON

FEATURE	PREMIUM 75	PREMIUM 90	PRESTIGE 75	PRESTIGE 95	PRESTIGE 75 PIVOT
 Frame Thickness	 75mm	 90mm	 75mm	 75mm	 75mm
 Sash Thickness	75mm	90mm	75mm	95mm	75mm
 Threshold Height	18,5mm	18mm	14mm	14mm	20mm + 30mm of frame extension to accommodate the pivot hinge
 Aluminium Thickness (door leaf)	2mm	2mm	3mm	3mm	3mm
 Minimum Overall Width	870mm	870mm	870mm	870mm	1250mm
 Minimum Overall Height	1900mm	1900mm	1900mm	1900mm	1900mm
 Maximum Overall Width	1250mm	1250mm	1300mm	1300mm	1600mm (2000mm on request)
 Maximum Overall Height	2300mm	2500mm	2500mm	2500mm	3200mm (4000mm on request)
 Produced in increments	5mm	5mm	1mm	1mm	1mm
 Door opens outwards	NO	YES	YES	YES	YES
 Standard Lock	Winkhaus 3 point	Winkhaus 5 point	GU 3 point	GU 3 point	GU 3 point slam-shut
 Hinge System	Wala	Wala	Dr. Hahn	Dr. Hahn	FritsJurgens M+
 Double Door	NO	NO	YES	NO	NO
 Triangle Top Light	NO	NO	YES	NO	YES
 Glass Type in the Door	Triple Glazed	Quadruple Glazed	Triple Glazed	Quadruple Glazed	Triple Glazed
 Escutcheon is flush with the panel surface	NO	NO	YES	YES	YES
 The strike plates are installed along the entire length.	NO	NO	YES	YES	YES